



PROJECT	TYPE
CATALOG NUMBER (FOR CUSTOM LENGTHS, PLEASE SEE ORDERING EXAMPLE BELOW)	

FEATURES

- 120V
- Wet location
- IC rating for insulated ceilings
- Edge-Lit technology for diode free illumination
- Dimmable (Triac)
- Shallow mount

ELECTRICAL

- 120V (remote power supply not required)
- Rated life: 50,000 hrs.

OPTICS

- 90+ CRI
- 120° beam angle

CERTIFICATION

- ETL
- Title 24
- Energy Star

WARRANTY

- 5 year warranty

PRODUCT DESCRIPTION

Easy to install with an included junction box that is connected via a modular jack, these 3", 4" and 6" slim mount, regressed downlights feature superior optics along with Energy Star rating in a streamlined, shallow mount design.



ORDERING INFORMATION

Catalog Number	Dimensions	Wattage	Lumens	CRI	Color Temp.*	Finish
RSD-3-27-WH	3-3/4" Dia. Trim	6W	300	90+	2700K	White
RSD-3-30-WH	3-3/4" Dia. Trim	6W	325	90+	3000K	White
RSD-3-40-WH	3-3/4" Dia. Trim	6W	355	90+	4000K	White
RSD-4-27-WH	5-1/8" Dia. Trim	9W	500	90+	2700K	White
RSD-4-30-WH	5-1/8" Dia. Trim	9W	525	90+	3000K	White
RSD-4-40-WH	5-1/8" Dia. Trim	9W	550	90+	4000K	White
RSD-6-27-WH	6-7/8" Dia. Trim	12W	700	90+	2700K	White
RSD-6-30-WH	6-7/8" Dia. Trim	12W	725	90+	3000K	White
RSD-6-40-WH	6-7/8" Dia. Trim	12W	750	90+	4000K	White

* Kelvin temperature (color) ±100K

ACCESSORIES

Catalog Number	Description
RSD-5FT-EXT	5' extension cord for RSD Series downlights
RSD-10FT-EXT	10' extension cord for RSD Series downlights
RSD-20FT-EXT	20' extension cord for RSD Series downlights

CUT-OUT DIMENSIONS

RSD-3: 3-1/4" DIA.
RSD-4: 4-1/4" DIA.
RSD-6: 6-1/8" DIA.

